FR-3300UV / FR-3300UVT

UV Solidified Roller Printing Machine

Machine configuration depending on different model. For more information, please call local dealer.

PRODUCT INTRODUCTION

- Adopting a four rubber roller transmission structure
- Benefiting from the environment-friendly UV LED curing technology
- Longer lifespan, lower energy consumption
- Soft/hard materials, one click switching

FR-3300UV / FR-3300UVT

UV Solidified Roller Printing Machine

Specifications

Machine configuration are different between models, Please consult your local distributor for more information

Items		Technical Parameters	
Model		FR-3300UV	FR-3300UVT
Print head	Print type	Industrial head	
	QTY	4-8	4-12
Ink	Color	C/M/Y/K/LC/LM/W	C/M/Y/K/LC/LM/W
	Ink type	UV ink	
	Ink supply	Pump ink supply	
Speed	Production mode	44 m^2/h	68 m^2/h
	Precision mode	34 m^2/h	42 m^2/h
	Photo mode	22 m^2/h	32 m^2/h
Media	Dimension	3200mm	3200mm
	Media type	Soft film, transparent film, backlit and frontlit flex, car stickers, textile fabrics and other printed materials	
	Media transfer	Feeding and taking up system with rubber rolls and high procession motors	
Cleaning		Positive pressure cleaning system	
Interface		USB	
Working Environment		Temperature: 18℃-30℃, Humidity : 30%-80%	
Power Supply		Frequency: 50HZ/60HZ	
		Rated voltage: AC220V (±10%)	
Machine Dimension		L5370 × W1330 × H1850 (mm)	
Machine Weight		2350Kg	2380Kg

Print speed varies over the computer, the media will have errors of different width to the actual subject.

Nanjing Meiyin Digital Technology Co., Ltd

Address: Building B, No. 8 Pengcheng Road, Jiangning District,
Nanjing City, Jiangsu Province, China

www.fornidigital.com admin@fornidigital.com