

FB-3220 / FB-3220T

UV Flatbed Printing Machine



Machine configuration depending on different model. For more information, please call local dealer.

PRODUCT INTRODUCTION



Equipment equipped with three rows of industrial piezoelectric optical nozzles



The platform has both suction and blowing functions, making it easy to move heavy boards



High end machine configuration with metal grating ruler and magnetic levitation motor system



Can choose 8 colors, supports simultaneous printing of 8 colors

FB-3220 / FB-3220T

UV Flatbed Printing Machine

FORNI

► Specifications

Machine configuration are different between models, Please consult your local distributor for more information

Items		Technical Parameters	
Model		FB-3220	FB-3220T
Print head	Print type	Ricoh industrial head/ Kyocera industrial head	
	QTY	4-12	4-10
Ink	Color	C/M/Y/K/LC/LM/W/V 支持白墨、光油打印	C/M/Y/K/LC/LM/W支持白墨打印
	Ink type	UV ink	
	Ink supply	Ink supply by pump	
Speed	Production mode	72 m ² /h	102 m ² /h
	Precision mode	56 m ² /h	78 m ² /h
	Photo mode	38 m ² /h	54 m ² /h
Media	Dimension	3200mm × 2000mm	3200mm × 2000mm
	Media type	Acrylic, Ceramic, Glass, Aluminum sheet, Wooden door, PVC sheet and Other Printing Materials	
	Media transfer	Platform	
Cleaning		Press buttons	
Interface		USB	
Working Environment		Temperature: 18°C-30°C, Humidity : 30%-80%	
Power Supply		Rated Frequency: 50HZ/60HZ Power : Maximum 7500W	
		Rated voltage: AC220V (±10%)	
Machine Dimension		L5500 × W2800 × H1400 (mm)	
Machine Weight		1950Kg	1970Kg

Print speed varies over the computer, the media will have errors of different width to the actual subject.

Nanjing Meiyin Digital Technology Co., Ltd

Address: Building B, No. 8 Pengcheng Road, Jiangning District,

Nanjing City, Jiangsu Province, China

www.fornidigital.com

admin@fornidigital.com